



## FEATURES:

- Fluorescent luminaire with direct-indirect lighting distribution.
- Lamp source: T5 or PL-L Fluorescent.
- Diffused illumination is provided by two micro-perforated wings with 2 3/4" deep 8 cell parabolic reflector.
- Excellent combination of direct and accent lighting.
- Suitable for recessed, suspended or surface mounted installations.
- Housing is made from 18Ga rolled steel.
- Has a proven record in office, commercial and retail applications.
- Custom modifications are available.
- ED luminaires are certified to CSA and UL standards.

## SPECIFICATION:

### 2x2 EDMEK05

#### LAMPS

2X14W T5  
2X24W T5  
2X25W PL  
2X40W PL  
2X50W PL  
2X55W PL

#### VOLTAGE

120V  
277V  
347V

#### BALLAST

ST - Standard  
IS - Instant Start  
RS -Rapid Start  
HO - High Output  
DM - Dimming  
DL - DALI

#### FINISH


RS - Recessed  
SF - Surface  
DR - Drywall  
AC - Aircraft

#### LOUVER

AL - Aluminum  
WH - White

## DIMENSIONS:

	RECESSED	SURFACE
Length:	23 3/4"	24 5/8"
Width:	23 3/4"	24 6/8"
Depth:	3 3/4"	4 1/2"



## OPTIONS:

### SURFACE



### WHITE



Project:

Type:

## Edison Lighting Group Ltd.

1303 Ringwell Dr. Unit #2, Newmarket, ON L3Y 8T9

Tel: 905-830-0339 or 1-800-667-9281 Fax: 905-898-6439 or 1-800-667-9302

www.edisonlighting.ca info@edisonlighting.ca