



## FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ Available with white aluminum reflector.
- ✓ Suitable for suspended installation.
- ✓ Aluminum body with integrated driver.
- ✓ Available in black or white finish.
- ✓ LED spot is rated for 60,000hrs. L80 with +90 CRI.
- ✓ Has a proven record in office and commercial installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

## SPECIFICATION:

**ED ZEN+**



Enter the Product Code into the boxes above.

### SOURCE

- 17 W
- 34 W

### RADIANCE

- DD - Direct

### VOLTAGE

- UNV - 120/277V

- 347V<sup>1</sup>

1. Verify availability.

### DRIVER

- ST - On/Off
- DL - 0-10V Dim (1%)
- DA4 - DALI D4i
- 

Specify dimming protocol.

### MOUNTING

- S6B - 6ft Cord BK<sup>1</sup>
- S6W - 6ft Cord WH<sup>1</sup>
- S   ft<sup>2</sup>

1. Canopy match the Cord color.  
2. Specify Suspension length/color.

### REFLECTOR

- AL - Aluminum

### FINISH

- BK - Black<sup>1</sup>

- WH - White<sup>2</sup>


1. RAL 9005

2. RAL 9003

### CCT

- 30K - 3000 Kelvin/90CRI
- 35K - 3500 Kelvin/90CRI
- 40K - 4000 Kelvin/90CRI
- 

Specify required CCT.



## DIMENSIONS:

Height	Width
13.75 in	12.25 in

## LUMEN OUTPUT:

Watts	30K	35K	40K
17 W	1950 lm	2000 lm	2050 lm
34 W	3900 lm	4000 lm	4100 lm



Project:

Type: