

**FEATURES:**

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: 11" LED modular board.
- ✓ Dark Optic provides superior lighting distribution with precise low-glare illumination.
- ✓ 7 cell LEDiL reflector is available in several standard finishes.
- ✓ Offered with Flood 50°/16UGR and Wide 80°/19UGR internal optics.
- ✓ Low profile steel body housing contains a built-in driver.
- ✓ Suitable for non-insulated recessed installations into T-Bar or drywall.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ LED's are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

**reinventlight**
**SPECIFICATION:**


Enter the Product Code into the boxes above.

**SOURCE**

20 W  
 30 W

**RADIANCE**

DD - Direct

**VOLTAGE**

UNV - 120/277V  
 347V<sup>1</sup>

1. Verify availability.

**DRIVER**

ST - On/Off  
 DL - 0-10V Dim (1%)  
 DLO - 0-10V Dim (to Off)  
 DLA - 0-10V Dim (Aux)  
 DA4 - DALI D4i

Specify dimming protocol.

**MOUNTING**

RS - Recessed

**BEAM**

BF - Flood 50°  
 BW - Wide 80°

**REFLECTOR**

SB - Black  
 SW - White

**FINISH**

BK - Black<sup>1</sup>  
 WH - White<sup>2</sup>

 1. RAL 9005  
 2. RAL 9003

**CCT**

30K - 3000 Kelvin/90CRI  
 35K - 3500 Kelvin/90CRI  
 40K - 4000 Kelvin/90CRI

Specify required CCT.

**OPTIONS**

No - Options<sup>1</sup>  
 EM - Emergency Battery<sup>2</sup>  
 JD - JDRF Autonomy Sensor (DA4)  
 DOS - Daylight & Occupancy Sensor (DLA)  
 AWN - Athena Wireless Node (DLA)


 1. Leave empty.  
 2. Emergency battery pack.  
 Specify required option.


BLACK

WHITE

**DIMENSIONS:**

Length	Width	Height
23.75 in	23.75 in	1.50 in


**LUMEN OUTPUT lm/W**

Watts	30K	35K	40K
20 W	2450 lm	2500 lm	2550 lm
30 W	3675 lm	3750 lm	3825 lm


**Project:**
**Type:**