



FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: LED board (5.5"/11"/22"/24").
- ✓ Diffused illumination is provided by high efficiency opal inserted or optional low glare micropismatic lens.
- ✓ Suitable for suspended and row mounted installations.
- ✓ Fixture body with integrated driver is made from light weight steel.
- ✓ Available with matt black or white finish.
- ✓ LED Strips are rated for 60,000hrs. L70 with +90 CRI.
- ✓ Has a proven record in office, commercial applications.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED EDGE+ — — — — — — — — —

Enter the Product Code into the boxes above.

SOURCE

- ☐ 35W LED
☐ 45W LED

RADIANCE

- ☐ DD - Direct (100%Down)
 *Light Distribution.

VOLTAGE

- ☐ 120V
☐ 277V
☐ 347V*
 *Not available for all configurations.

DRIVER

- ☐ ST - Standard (Non-Dimming)
☐ DL - 0-10V Dimming (1%)
☐ DA - DALI
☐ *
 *Please specify dimming method.

MOUNTING

- ☐ S4-Suspension 4Feet
☐ S6-Suspension 6Feet
☐ S Feet*
☐ SF - Surface Mount
 *Please specify required Length.

LENS

- ☐ OP - Opal
☐ PR - Prismatic

FINISH

- ☐ BK - Black
☐ WH - White

CCT

- ☐ 30K - 3000Kelvin/90CRI
☐ 35K - 3500Kelvin/90CRI
☐ 40K - 4000Kelvin/90CRI
☐ RGBW*
☐ TW - Tunable White**
 (2700K-6500K)

*Available with Dali.
 **Available with 0-10V,Dali controls.

OPTIONS

- ☐ DOS - Daylight & Occupancy Sensor*
 *With compatible DALI driver.

DIMENSIONS:

Length	Width	Depth
47.25"	7.125"	2.250"

LUMEN OUTPUT:

Watts	30K	35K	40K
35W	3420lm	3500 lm	3580 lm
45W	4400 lm	4500 lm	4600 lm

