

FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency low glare integral reflector comes in following beam angles: Narrow 15°, Medium Flood 35° and Flood 55°.
- ✓ Adjustable trim assembly can be tilted up to 30° for wall wash applications.
- ✓ Available with optional flat frame plate for NC installations.
- ✓ Suitable for recessed insulated ceilings or damp locations.
- ✓ LED spot is rated for 60,000 hrs. L70 with +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED SD+ — — — — — — — — —

Enter the Product Code into the boxes above.

SIZE

- ☐ 2x-Double

SOURCE

- ☐ 15W LED
☐ 20W LED
☐ 25W LED

RADIANCE

- ☐ DD - Direct (100%Down)
*Light Distribution.

VOLTAGE

- ☐ 120V
☐ 277V
☐ 347V*

*Not available for all configurations.

DRIVER

- ☐ ST - Standard (Non-Dimming)
☐ DL - 0-10V Dimming (1%)
☐ DA4 - DALI D4i
☐ *

* Please specify dimming method.

MOUNTING

- ☐ RT -Retrofit
☐ NC- New Const. Plate

BEAM

- ☐ BN - Narrow 15°
☐ BM - Medium 35°
☐ BF - Flood 55°

REFLECTOR

- ☐ MW - Matte White
☐ MB - Matte Black
☐ MS - Matte Silver

TRIM

- ☐ WH - White
☐ BK - Black
☐ GR - Grey


CCT

- ☐ 30K/90CRI - 3000 Kelvin
☐ 35K/90CRI - 3500 Kelvin
☐ 40K/90CRI - 4000 Kelvin
☐ *

*Specify required CCT.

DIMENSIONS:

Size	Height	Width	Length	Cut Out
Double	4.88"	4.13"	7.69"	7.48" x 3.82"



LUMEN OUTPUT:

Watts	30K	35K	40K
15W	1425 lm	1455 lm	1485 lm
20W	1900 lm	1940 lm	1980 lm
25W	2375 lm	2425 lm	2475 lm



Project:

Type: