

FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: 11" LED modular board.
- ✓ Dark Optic provides superior lighting distribution with precise low-glare illumination.
- ✓ 7 cell LEDiL reflector is available in several standard finishes.
- ✓ Offered with Flood 50°/16UGR and Wide 80°/19UGR internal optics.
- ✓ Low profile steel body housing contains a built-in driver.
- ✓ Suitable for non-insulated recessed installations into T-Bar or drywall.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ LED's are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

SPECIFICATION:

ED LINE2+

SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	BEAM	REFLECTOR	FINISH	CCT	OPTIONS
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Enter the Product Code into the boxes above.

SOURCE

- ☐ 20W LED
- ☐ 30W LED

RADIANCE

- ☐ DD - Direct (100%Down)
- *Light Distribution.

VOLTAGE

- ☐ 120V
 - ☐ 277V
 - ☐ 347V*
- * Not available for all configurations.

DRIVER

- ☐ ST - On/Off
 - ☐ DL - 0-10V Dimming (1%)
 - ☐ DLO - 0-10V Dimming (to Off)
 - ☐ DA4 - DALI D4i
 - ☐ EM - Emergency Driver*
 - ☐ **
- *Emergency battery pack.
**Specify dimming protocol.

MOUNTING

- ☐ RS - Recessed
- ☐ DW - Drywall

BEAM

- ☐ BF - Flood 50°
- ☐ BW - Wide 80°

REFLECTOR

- ☐ SB - Black
- ☐ SW - White
- ☐ SR - Red
- ☐ SL - Silver
- ☐ SG - Gold
- ☐ SM - Gunmetal

FINISH

- ☐ BK - Black*
 - ☐ WH - White**
- *RAL 9005
**RAL 9003

CCT

- ☐ 30K/90CRI - 3000 Kelvin
 - ☐ 35K/90CRI - 3500 Kelvin
 - ☐ 40K/90CRI - 4000 Kelvin
 - ☐ *
- *Specify required CCT.

OPTIONS

- ☐ No Options*
 - ☐ CB - Casambi/Bluetooth
 - ☐ ***
- *Leave empty.
**Specify required option.



BLACK



WHITE



RED



SILVER



GOLD




GUNMETAL

DIMENSIONS:

Length	Width	Height
23.75"	23.75"	1.50"

LUMEN OUTPUT:

Watts	30K	35K	40K
20W	2450lm	2500lm	2550lm
30W	3675lm	3750lm	3825lm



Project:

Type: