

**FEATURES:**

- ✓ Architectural linear luminaire with direct-indirect lighting distribution.
- ✓ Light source: LED Tape.
- ✓ Sleek X-shape design is a unique blend between extruded aluminum body and high efficiency opal lens.
- ✓ Suitable for surface,suspended,wall mounted installations.
- ✓ Offered with integrated built-in LED driver.
- ✓ Aluminum body comes with white, black or grey finish.
- ✓ LED Tape are rated for 60,000hrs. L80 with +90 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

**SPECIFICATION:**

**ED SANT+**  -  -  -  -  -  -  -  -  -  -

Enter the Product Code into the boxes above.

**SIZE\***

- 4Feet
- 6Feet
- 8Feet

\*Not suitable for row mounting.

**SOURCE**

- 5W/Ft LED
- 7W/Ft LED
- 10W/Ft LED

**RADIANCE**

- DI - Direct Indirect (85%Down-15%Up)

\*Light Distribution.

**VOLTAGE**

- 120V
- 277V
- 347V\*

\*Not available for all configurations.

**DRIVER**

- ST - Standard (Non-Dimming)
- DL - 0-10V Dimming (1%)
- DA - DALI
- BT - Bluetooth
- \*

\*Please specify dimming method.

**MOUNTING**

- S4-Suspension 4Feet
- S6-Suspension 6Feet
- S  Feet\*
- WF - Wall Flush
- SF - Surface Mount

\*Please specify required Length.

**LENS**

- OP - Opal

**FINISH**

- WH - White
- BK - Black
- GR - Grey
- CF - Custom  RAL#

**CCT**

- 30K/90CRI - 3000Kelvin
- 35K/90CRI - 3500Kelvin
- 40K/90CRI - 4000Kelvin
- RGBW\*
- TW - Tunable White\*\*  
(2700K-6500K)

\*Available with Dali, DMX or Bluetooth controls.

\*\*Available with 0-10V,Dali or Bluetooth controls.

**OPTIONS**

- DOS - Daylight & Occupancy Sensor\*


\*With compatible DALI driver.

**LENGTH CHART**

Size	Length
4 Feet	47.75 Inch
6 Feet	71.75 Inch
8 Feet	95.75 Inch

**LUMEN OUTPUT W/Ft:**

Watts	30K	35K	40K
5W	515 lm	525 lm	535 lm
7W	720 lm	735 lm	750 lm
10W	1030lm	1050 lm	1080 lm



Project:

Type: