

FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: 11" LED modular board.
- ✓ Dark Optic provides superior lighting distribution with precise low-glare illumination.
- ✓ 7 cell LEDiL reflector is available in several standard finishes.
- ✓ Offered with Flood 50°/16UGR and Wide 80°/19UGR internal optics.
- ✓ Low profile steel body housing contains a built-in driver.
- ✓ Suitable for non-insulated recessed installations into T-Bar or drywall.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ LED's are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

SPECIFICATION:

ED LINE2+ — — — — — — — — — —

Enter the Product Code into the boxes above.

SOURCE

- ☐ 10W LED
☐ 20W LED

RADIANCE

- ☐ DD - Direct (100%Down)
 *Light Distribution.

VOLTAGE

- ☐ 120V
☐ 277V
☐ 347V*
 * Not available for all configurations.

DRIVER

- ☐ ST - On/Off
☐ DL - 0-10V Dim (1%)
☐ DLO - 0-10V Dim (to Off)
☐ DA4 - DALI D4i
☐ EM - Emergency Driver*
☐ **
 *Emergency battery pack.
 **Specify dimming protocol.

MOUNTING

- ☐ RS - Recessed
☐ DW - Drywall

BEAM

- ☐ BF - Flood 50°
☐ BW - Wide 80°

REFLECTOR

- ☐ SB - Black
☐ SW - White
☐ SR - Red
☐ SL - Silver
☐ SG - Gold
☐ SM - Gunmetal

FINISH

- ☐ BK - Black*
☐ WH - White**
 *RAL 9005
 **RAL 9003

CCT

- ☐ 30K - 3000 Kelvin/90CRI
☐ 35K - 3500 Kelvin/90CRI
☐ 40K - 4000 Kelvin/90CRI
☐ *
 *Specify required CCT.

OPTIONS

- ☐ No Options*
☐ CB - Casambi/Bluetooth
☐ **
 *Leave empty.
 **Specify required option.



BLACK



WHITE



RED



SILVER



GOLD




GUNMETAL

DIMENSIONS:

Length	Width	Height
23.75"	23.75"	1.50"

LUMEN OUTPUT:

Watts	30K	35K	40K
10W	1320 lm	1350 lm	1380 lm
20W	2635 lm	2700 lm	2765 lm



Project:

Type: