




FEATURES:

- ✓ Architectural acoustic luminaire with direct/indirect lighting distribution.
- ✓ Made from recyclable plastic material available in different thicknesses.
- ✓ Class 1 fire rated with 0.7 Noise Reduction Coefficient / 1" Acoustic.
- ✓ Light source: LED boards.
- ✓ Diffused illumination is provided by a frosted opal lens.
- ✓ Extruded aluminum body comes with a built-in-driver and available in a black or white finish.
- ✓ LED strips are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

SPECIFICATION:

Sonic VECTOR+

TYPE	HEIGHT	SIZE	SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	LENS	VECTOR FINISH	CCT	ACOUSTIC

Enter the Product Code into the boxes above

TYPE

- ☐ FR - Flush Regular
- ☐ FV - Flush V-Cut

HEIGHT

- ☐ 12 in
- ☐ 16 in
- ☐ 24 in

SIZE

- ☐ 4 ft
 - ☐ 6 ft
 - ☐ 8 ft
 - ☐
- Specify custom size.

SOURCE

- ☐ 5 W/ft
- ☐ 7 W/ft
- ☐ 10 W/ft

RADIANCE

- ☐ DD - Direct¹
 - ☐ ID - Indirect²
 - ☐ UD - Uneven³
1. 100%Down
2. 100%Up
3. 70%Down/30%Up

VOLTAGE

- ☐ UNV - 120/277V
 - ☐ 347V¹
1. Verify availability.

DRIVER

- ☐ ST - On/Off
 - ☐ DL - 0-10V Dim (1%)
 - ☐ DLO - 0-10V Dim (to Off)
 - ☐ DL2 - 0-10V Dim (TW)
 - ☐ CV - Constant Voltage (RGBW)
 - ☐
- Specify dimming protocol.

MOUNTING

- ☐ S6B - 6 ft Cord BK¹
 - ☐ S6W - 6 ft Cord WH¹
 - ☐ S ft²
1. Canopy match the Cord Color
2. Specify Suspension Length/color.

LENS

- ☐ OP - Opal

ED VECTOR+ FINISH

- ☐ BK - Black¹
 - ☐ WH - White²
1. RAL 9005
2. RAL 9016

CCT

- ☐ 30K - 3000 Kelvin/90CRI
 - ☐ 35K - 3500 Kelvin/90CRI
 - ☐ 40K - 4000 Kelvin/90CRI
 - ☐ RGBW¹
 - ☐ TW - Tunable White (27K-65K)²
 - ☐
1. Available with CV.
2. Available with DL2.
Specify required CCT.

ACOUSTIC FINISH

Specify additional color for Two-Tone, for example 04/11.



LUMEN OUTPUT W/ft:

Watts	30K	35K	40K
5 W	515 lm	525 lm	535 lm
7 W	720 lm	735 lm	750 lm
10 W	1030 lm	1050 lm	1080 lm




Declare.

Project:

Type:




SIZE:




H-Height	S-Size
12 in = 11.75 in	4 ft = 47.75 in
16 in = 15.75 in	6 ft = 71.75 in
24 in = 23.75 in	8 ft = 95.75 in

SL : Suspension Length


RADIANCE:




TYPE:




FR - Regular - 04




FR - 04/11




FR - 07




FR - 07/01




FV - V-Cut - 04



FV - 04/11



FV - 07



FV - 07/01