

FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: 11" Curved LED board.
- ✓ Dark Optic provides superior lighting distribution with precise low-glare illumination.
- ✓ 7 cell LEDiL curved reflector is available in several standard finishes.
- ✓ Offered with Flood 50°/16UGR and Wide 80°/19UGR internal optics.
- ✓ Low profile steel body housing contains a built-in driver.
- ✓ Suitable for non-insulated recessed installations into T-Bar or drywall.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ LED's are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

SPECIFICATION:

ED LINE 0+ SOURCE — RADIANCE — VOLTAGE — DRIVER — MOUNTING — BEAM — REFLECTOR — FINISH — CCT — OPTIONS

Enter the Product Code into the boxes above.

SOURCE

- ☐ 20W LED
- ☐ 30W LED
- ☐ 40W LED

RADIANCE

- ☐ DD - Direct (100%Down)
- *Light Distribution.

VOLTAGE

- ☐ 120V
 - ☐ 277V
 - ☐ 347V*
- * Not available for all configurations.

DRIVER

- ☐ ST - On/Off
 - ☐ DL - 0-10V Dim (1%)
 - ☐ DLO - 0-10V Dim (to Off)
 - ☐ DA4 - DALI D4i
 - ☐ EM - Emergency Driver*
 - ☐ **
- *Emergency battery pack.
**Specify dimming protocol.

MOUNTING

- ☐ RS - Recessed
- ☐ DW - Drywall

BEAM

- ☐ BF - Flood 50°
- ☐ BW - Wide 80°

REFLECTOR

- ☐ SB - Black
- ☐ SW - White
- ☐ SL - Silver

FINISH

- ☐ BK - Black*
 - ☐ WH - White**
- *RAL 9005
**RAL 9003

CCT

- ☐ 30K - 3000 Kelvin/90CRI
 - ☐ 35K - 3500 Kelvin/90CRI
 - ☐ 40K - 4000 Kelvin/90CRI
 - ☐ *
- *Specify required CCT.

OPTIONS

- ☐ No Options*
 - ☐ CB - Casambi/Bluetooth
 - ☐ **
- *Leave empty.
**Specify required option.



BLACK



WHITE



SILVER

DIMENSIONS:

Length	Width	Height	Radius
23.75"	23.75"	1.50"	7.00"

LUMEN OUTPUT:


Watts	30K	35K	40K
20W	1320 lm	1350 lm	1380 lm
30W	2635 lm	2700 lm	2765 lm
40W	3950 lm	4050 lm	4150 lm



Declare.

h

w



Project:

Type: