

### FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: 11" LED modular board.
- ✓ Dark Optic provides superior lighting distribution with precise low-glare illumination.
- ✓ 7 cell LEDiL reflector is available in several standard finishes.
- ✓ Offered with Flood 50°/16UGR and Wide 80°/19UGR internal optics.
- ✓ Low profile steel body housing contains a built-in driver.
- ✓ Suitable for non-insulated recessed installations into T-Bar or drywall.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ LED's are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

### SPECIFICATION:

**ED LINE4+**

SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	BEAM	REFLECTOR	FINISH	CCT	OPTIONS
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Enter the Product Code into the boxes above.

#### SOURCE

- ☐ 20W LED
- ☐ 30W LED
- ☐ 40W LED

#### RADIANCE

- ☐ DD - Direct (100%Down)
- \*Light Distribution.

#### VOLTAGE

- ☐ 120V
  - ☐ 277V
  - ☐ 347V\*
- \* Not available for all configurations.

#### DRIVER

- ☐ ST - On/Off
- ☐ DL - 0-10V Dim (1%)
- ☐ DLO - 0-10V Dim (to Off)
- ☐ DA4 - DALI D4i
- ☐ EM - Emergency Driver\*
- ☐  \*\*

\*Emergency battery pack.  
\*\*Specify dimming protocol.

#### MOUNTING

- ☐ RS - Recessed
- ☐ DW - Drywall

#### BEAM

- ☐ BF - Flood 50°
- ☐ BW - Wide 80°

#### REFLECTOR

- ☐ SB - Black
- ☐ SW - White
- ☐ SR - Red
- ☐ SL - Silver
- ☐ SG - Gold
- ☐ SM - Gunmetal

#### FINISH

- ☐ BK - Black\*
  - ☐ WH - White\*\*
- \*RAL 9005  
\*\*RAL 9003

#### CCT

- ☐ 30K - 3000 Kelvin/90CRI
- ☐ 35K - 3500 Kelvin/90CRI
- ☐ 40K - 4000 Kelvin/90CRI
- ☐  \*

\*Specify required CCT.

#### OPTIONS

- ☐ No Options\*
- ☐ CB - Casambi/Bluetooth
- ☐  \*\*

\*Leave empty.  
\*\*Specify required option.



BLACK



WHITE



RED



SILVER



GOLD



GUNMETAL

### DIMENSIONS:


Length	Width	Height
23.75"	23.75"	1.50"

### LUMEN OUTPUT:

Watts	30K	35K	40K
20W	1320 lm	1350 lm	1380 lm
30W	2635 lm	2700 lm	2765 lm
40W	3950 lm	4050 lm	4150 lm



Declare



Project:

Type: