


**FEATURES:**

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: LED boards.
- ✓ Diffused illumination is provided by high efficiency frosted opal lens.
- ✓ Sleek body of the luminaire combines two aluminum side with laser cut metal top enclosure.
- ✓ Suitable for non-insulated recessed installations.
- ✓ Extruded aluminum body comes with a black or white finish.
- ✓ Also available with custom color options.
- ✓ LED Boards are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

**reinventlight**
**SPECIFICATION:**
**ED RING+**


Enter the Product Code into the boxes above.

**SIZE**

2 ft  
 3 ft  
 4 ft  
  Specify custom size.

**SOURCE**

25 W  
 50 W  
 75 W<sup>1</sup>

1. Available for 4ft & Custom sizes.  
2. Other Wattages are available.

**RADIANCE**

DD - Direct

**VOLTAGE**

UNV - 120/277V  
 347V<sup>1</sup>

1. Verify availability.

**DRIVER**



ST - On/Off  
 DL - 0-10V Dim (1%)  
 DLO - 0-10V Dim (to Off)  
 DL2 - 0-10V Dim (TW)  
 DLA - 0-10V Dim (Aux)  
 DA4 - DALI D4i  
 CV - Constant Voltage (RGBW)  
  Specify dimming protocol.

**MOUNTING**

RS - Recessed

**LENS**

OP - Opal


**FINISH**

BK - Black<sup>1</sup>  
 WH - White<sup>2</sup>  
 CF/RAL

1. RAL 9005  
2. RAL 9003  
Specify required RAL number.

**CCT**

30K - 3000 Kelvin/90CRI  
 35K - 3500 Kelvin/90CRI  
 40K - 4000 Kelvin/90CRI  
 RGBW<sup>1</sup>  
 TW - Tunable White (27K-65K)<sup>2</sup>

1. Available with DMX or CB.  
2. Available with DL2, DA4 or CB.  
Specify required CCT.

**OPTIONS**

No Options<sup>1</sup>  
 EC - Emergency Circuit  
 CB - Casambi Bluetooth(TW, RGBW)  
 DMX - DMX (RGBW)  
 AWN - Athena Wireless Node (DLA)

1. Leave empty.

Size	Cutaway Diameters	
	OD <sub>(Outer Diameter)</sub>	ID <sub>(Inner Diameter)</sub>
2 ft	25.98 in	21.26 in
3 ft	35.43 in	30.71 in
4 ft	47.24 in	42.52 in

**Project:**
**Type:**
**LUMEN OUTPUT:**

Watts	30K	35K	40K
25 W	2205 lm	2250 lm	2295 lm
50 W	4410 lm	4500 lm	4590 lm
75 W	6610 lm	6750 lm	6890 lm



Declare.