




FEATURES:

- ✓ Architectural luminaire with direct/indirect lighting distribution.
- ✓ Light source: COB LED.
- ✓ Extremely durable round diffuser is made from frosted PMMA polycarbonate for even lighting distribution.
- ✓ Steel body with built-in-driver, available in black or white finish.
- ✓ Suitable for surface and wall mounted installations.
- ✓ LED spot is rated for 60,000hrs. L70 with +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:



Enter the Product Code into the boxes above.

SOURCE

- 15W LED
- 20W LED
- 30W LED

RADIANCE

- DI - Direct Indirect (85%DN/15%Up)
*Light Distribution.

VOLTAGE

- 120V
 - 277V
 - 347V*
- *Not available for all configurations.

DRIVER

- ST - Standard (Non-Dimming)
 - DL - 0-10V Dimming (1%)
 - DA - DALI
 - *
- *Please specify dimming method.

MOUNTING

- WM -Wall Mount
- CM-Ceiling Mount

LENS

- OP - Opal

FINISH


- BK - Black
- WH - White

CCT


- 30K - 3000Kelvin/90CRI
 - 35K -3500Kelvin/90CRI
 - 40K - 4000Kelvin/90CRI
- *Other options are available.

DIMENSIONS:

Height	Width
2.375"	11.5"



W



h

LUMEN OUTPUT:

Watts	30K	35K	40K
15W	1360 lm	1400 lm	1440 lm
20W	1850 lm	1900 lm	1950 lm
30W	2800 lm	2900 lm	3000 lm



Project:

Type: