

## FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: 11" LED modular board.
- ✓ Dark Optic provides superior lighting distribution with precise low-glare illumination.
- ✓ 7 cell LEDiL reflector is available in several standard finishes.
- ✓ Offered with Flood 50°/16UGR and Wide 80°/19UGR internal optics.
- ✓ Low profile steel body housing contains a built-in driver.
- ✓ Suitable for non-insulated recessed installations into T-Bar or drywall.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ LED's are rated for 60,000hrs. L80 with +90 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

## SPECIFICATION:

**ED LINE3+**

SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	BEAM	REFLECTOR	FINISH	CCT	OPTIONS
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Enter the Product Code into the boxes above.

### SOURCE

- ☐ 20W LED
- ☐ 30W LED
- ☐ 40W LED

### RADIANCE

- ☐ DD - Direct (100%Down)
- \*Light Distribution.

### VOLTAGE

- ☐ 120V
  - ☐ 277V
  - ☐ 347V\*
- \* Not available for all configurations.

### DRIVER

- ☐ ST - On/Off
- ☐ DL - 0-10V Dimming (1%)
- ☐ DLO - 0-10V Dimming (to Off)
- ☐ DA4 - DALI D4i
- ☐ EM - Emergency Driver\*
- ☐  \*\*

\*Emergency battery pack.  
\*\*Specify dimming protocol.

### MOUNTING

- ☐ RS - Recessed
- ☐ DW - Drywall

### BEAM

- ☐ BF - Flood 50°
- ☐ BW - Wide 80°

### REFLECTOR

- ☐ SB - Black
- ☐ SW - White
- ☐ SR - Red
- ☐ SL - Silver
- ☐ SG - Gold
- ☐ SM - Gunmetal

### FINISH

- ☐ BK - Black\*
  - ☐ WH - White\*\*
- \*RAL 9005  
\*\*RAL 9003

### CCT

- ☐ 30K/90CRI - 3000 Kelvin
- ☐ 35K/90CRI - 3500 Kelvin
- ☐ 40K/90CRI - 4000 Kelvin
- ☐  \*

\*Specify required CCT.

### OPTIONS

- ☐ No Options\*
- ☐ CB - Casambi/Bluetooth
- ☐  \*\*\*

\*Leave empty.  
\*\*Specify required option.



BLACK



WHITE



RED



SILVER



GOLD



GUNMETAL

## DIMENSIONS:


Length	Width	Height
23.75"	23.75"	1.50"

## LUMEN OUTPUT:

Watts	30K	35K	40K
20W	2450lm	2500lm	2550lm
30W	3675lm	3750lm	3825lm
40W	4900lm	5000lm	5100lm



Declare



Project:

Type: