



FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: LED Module.
- ✓ Unique multioptic lens provide superior lighting distribution with Unified Glare Rating of <19 URG.
- ✓ Ideal for computerized offices and educational institutional.
- ✓ Suitable for suspended installation with remote driver.
- ✓ Low profile steel body is available in black or white finish.
- ✓ LED's are rated for 60,000hrs. L70 with +90 CRI.
- ✓ Standard suspension length is 96 Inch.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED RAYS+ SOURCE — RADIANCE — VOLTAGE — DRIVER — MOUNTING — LENS — FINISH — CCT — OPTIONS

Enter the Product Code into the boxes above.

SOURCE

- ☐ 25W LED
☐ 35W LED

RADIANCE

- ☐ DD - Direct (100%Down)
 *Light Distribution.

VOLTAGE

- ☐ 120V
☐ 277V
☐ 347V*

*Not available for all configurations.

DRIVER

- ☐ ST - Standard (Non-Dimming)
☐ DL - 0-10V Dimming (1%)
☐ DA - DALI
☐ *

*Please specify dimming method.

MOUNTING

- ☐ S4-Suspension 4Feet
☐ S6-Suspension 6Feet
☐ S Feet*

*Please specify required Length.

LENS

- ☐ OP - Opal

FINISH

- ☐ BK - Black
☐ WH - White

CCT

- ☐ 30K - 3000Kelvin/90CRI
☐ 35K - 3500Kelvin/90CRI
☐ 40K - 4000Kelvin/90CRI

*Other options are available.

OPTIONS

- ☐ DOS - Daylight & Occupancy Sensor*
 *With compatible DALI driver.

DIMENSIONS:

Length	Width	Depth
47.25"	3.5"	0.5"

LUMEN OUTPUT:

Watts	30K	35K	40K
25W	2800 lm	2875 lm	2950 lm
35W	3925 lm	4025 lm	4125 lm

