



FEATURES:

- ✓ Architectural adjustable luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency optical system is available with 20° Narrow, 40° Flood or 60° Wide Beam Angle.
- ✓ An integrated TRIAC/ELV dimming driver is placed into a sleek minimalistic body of the luminaire.
- ✓ Available in a black or white finish.
- ✓ Comes standard with Juno track adapter.
- ✓ LED spot is rated for 60,000 hrs. L80 with a +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

SPECIFICATION:

ED TRS+

SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	BEAM	FINISH	CCT

Enter the Product Code into the boxes above.

SOURCE

- ☐ 10 W

RADIANCE

- ☐ DD - Direct

VOLTAGE

- ☐ 120V

DRIVER

- ☐ ST - On/Off
☐ DT - TRIAC
☐

Specify required dimming method.

MOUNTING

- ☐ JT-Juno Track
☐

Specify track adapter.

BEAM

- ☐ BN - Narrow 20°
☐ BF - Flood 40°
☐ BW - Wide 60°

FINISH

- ☐ BK - Black¹
☐ WH - White²
 1. RAL 9005
 2. RAL 9016

CCT

- ☐ 30K - 3000 Kelvin/90CRI
☐ 35K - 3500 Kelvin/90CRI
☐ 40K - 4000 Kelvin/90CRI
☐


Specify required CCT.

DIMENSIONS:

Height	Width	Diameter
5.500 in	4.125 in	2.375 in

LUMEN OUTPUT:

Watts	30K	35K	40K
10 W	950 lm	1000 lm	1050 lm



Project:

Type: