

FEATURES:

- ✓ Architectural linear luminaire with direct distribution.
- ✓ Light source: LED board or LED strip.
- ✓ Even illumination is provided by a variety of high-efficiency optic lenses.
- ✓ Available for row-mounted installations in various lengths.
- ✓ Suitable for recessed applications in drywall or T-Bar ceilings.
- ✓ Extruded aluminum body comes with a standard black or white finish.
- ✓ Also available with various custom color options.
- ✓ LED strips are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

SPECIFICATION:

ED VECTOR+ SIZE — SOURCE — RADIANCE — VOLTAGE — DRIVER — MOUNTING — LENS — FINISH — CCT — OPTIONS

Enter the Product Code into the boxes above.

SIZE

_____ Ft*
 *1-8 Ft
 Continuous Run
 (0.5 Ft Increments)

SOURCE

- ☐ 5 W/Ft
☐ 7 W/Ft
☐ 10 W/Ft

RADIANCE

- ☐ DD - Direct (100%Down)
 *Light Distribution.

VOLTAGE

- ☐ UNV - 120/277V
☐ 347V*
 *Not available for all configurations.

DRIVER

- ☐ ST - On/Off
☐ DL - 0-10V Dim (1%)
☐ DLO - 0-10V Dim (to Off)
☐ DL2 - 0-10V Dim (TW)
☐ DA4 - DALI D4i
☐ DMX - DMX RGBW
☐ EM - Emergency Driver*
☐ **

*Battery Pack min. 4 Ft section.
 **Specify dimming protocol.

MOUNTING

- ☐ RS - Recessed
☐ RB - Recessed T-Bar

LENS

- ☐ OP - Opal
☐ AS - Asymmetric
☐ PR - Prismatic

FINISH

- ☐ BK - Black*
☐ WH - White**
☐ CF/RAL ***
 *RAL 9005
 **RAL 9016
 ***Specify required RAL number.

CCT

- ☐ 30K - 3000 Kelvin/90CRI
☐ 35K - 3500 Kelvin/90CRI
☐ 40K - 4000 Kelvin/90CRI
☐ RGBW
☐ TW - Tunable White*
 (2700K-6500K)
☐ **
 *Available with 0-10V, Dali or Bluetooth controls.
 **Specify required CCT.

OPTIONS

- ☐ No Options*
☐ DR - Damp Rated
☐ CB - Casambi/Bluetooth
☐ JD - JDRF Autonomy Sensor
☐ DOS - Daylight & Occupancy Sensor
☐ **
 *Leave empty.
 **Specify required option.

LUMEN OUTPUT W/Ft:


Watts	30K	35K	40K
5W	515 lm	525 lm	535 lm
7W	720 lm	735 lm	750 lm
10W	1030lm	1050 lm	1080 lm



Project:

Type:

SIZE:




Size	L(EXTRUSION LENGTH)	L1(T-BAR)
1 Ft	11.50 In	11.75 In
2 Ft	24.25 In	23.75 In
3 Ft	35.25 In	35.75 In
4 Ft	40.75 In	47.75 In
5 Ft	59.00 In	59.75 In
6 Ft	71.75 In	71.75 In
7 Ft	82.75 In	83.75 In
8 Ft	95.50 In	95.75 In

*Total length with endcaps = L + 0.22"
 **Total length with endcaps for Recessed installation.
 ***L1 is total length with trim for T-Bar installation.


CONTINUOUS RUN:



RADIANCE:




MOUNTING:




RECESSED

RS - Recessed Bracket
 PO - Power Opening
 *Cutout Dimensions = Total Length L x Width of Extrusion.




90° IN (WALL TO CEILING)



RECESSED T-BAR

RB - Recessed T-BAR Bracket
 PO - Power Opening
 *Cutout Dimensions = Total Length L1 x Width of Extrusion.



VARIABLE ANGLE

60°, 90°, 120°, 135° or Custom.