

## FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: 11" Curved LED board.
- ✓ Dark Optic provides superior lighting distribution with precise low-glare illumination.
- ✓ 7 cell LEDiL curved reflector is available in several standard finishes.
- ✓ Offered with Flood 50°/16UGR and Wide 80°/19UGR internal optics.
- ✓ Low profile steel body housing contains a built-in driver.
- ✓ Suitable for non-insulated recessed installations into T-Bar or drywall.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ LED's are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

## SPECIFICATION:

**ED LINE 0+**  —  —  —  —  —  —  —  —  —  —

Enter the Product Code into the boxes above.

### SOURCE

- ☐ 20 W  
☐ 30 W  
☐ 40 W

### RADIANCE

- ☐ DD - Direct (100%Down)  
 \*Light Distribution.

### VOLTAGE

- ☐ UNV - 120/277V  
☐ 347V\*  
 \*Not available for all configurations.

### DRIVER

- ☐ ST - On/Off  
☐ DL - 0-10V Dim (1%)  
☐ DLO - 0-10V Dim (to Off)  
☐ DA4 - DALI D4i  
☐ EM - Emergency Driver\*  
☐  \*\*  
 \*Emergency battery pack.  
 \*\*Specify dimming protocol.

### MOUNTING

- ☐ RS - Recessed  
☐ DW - Drywall

### BEAM

- ☐ BF - Flood 50°  
☐ BW - Wide 80°

### REFLECTOR

- ☐ SB - Black  
☐ SW - White  
☐ SL - Silver

### FINISH

- ☐ BK - Black\*  
☐ WH - White\*\*  
 \*RAL 9005  
 \*\*RAL 9003

### CCT

- ☐ 30K - 3000 Kelvin/90CRI  
☐ 35K - 3500 Kelvin/90CRI  
☐ 40K - 4000 Kelvin/90CRI  
☐  \*  
 \*Specify required CCT.

### OPTIONS

- ☐ No Options\*  
☐ CB - Casambi/Bluetooth  
☐  \*\*  
 \*Leave empty.  
 \*\*Specify required option.





## DIMENSIONS:

| Length | Width  | Height | Radius |
|--------|--------|--------|--------|
| 23.75" | 23.75" | 1.50"  | 7.00"  |

## LUMEN OUTPUT:

| Watts | 30K     | 35K     | 40K     |
|-------|---------|---------|---------|
| 20 W  | 1320 lm | 1350 lm | 1380 lm |
| 30 W  | 2635 lm | 2700 lm | 2765 lm |
| 40 W  | 3950 lm | 4050 lm | 4150 lm |



Project:

Type: