



FEATURES:

- ✓ Architectural luminaire with direct-indirect lighting distribution.
- ✓ Light source: LED Tape.
- ✓ Diffused illumination is provided by high efficiency frosted opal lens.
- ✓ Sleek body of the luminaire is made from curved aluminum profile.
- ✓ Suitable for suspended and surface mounted installations.
- ✓ Extruded aluminum body comes with white, black or grey finish.
- ✓ Remote driver is mounted in round ceiling canopy or optional rectangle enclosure.
- ✓ LED tape is rated for 50,000hrs. L80 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED ORBIT+ — — — — — — — — —

Enter the Product Code into the boxes above.

SIZE

- ☐ 2 Feet
☐ 3 Feet
☐ 4 Feet
☐ *

* Please specify required size.

SOURCE

- ☐ 25WLED
☐ 50WLED
☐ 75WLED*

*Available for 4 Feet.

**Other Wattages are available.

RADIANCE

- ☐ IL - Inner Lit (100% Inward)
☐ OL - Outer Lit (100% Outward)

*Light Distribution.

VOLTAGE

- ☐ 120V
☐ 277V
☐ 347V*

*Not available for all configurations.

DRIVER

- ☐ ST - Standard
☐ DL - 0-10V Dimming (1%)
☐ DA - DALI
☐ *

* Please specify dimming method (ELV).

MOUNTING

- ☐ C4-Canopy 4Feet
☐ C6-Canopy 6Feet
☐ C Feet*
☐ D4-Drop 4Feet
☐ D6-Drop 6Feet
☐ D Feet*
☐ S4-Suspension 4Feet**
☐ S6-Suspension 6Feet**
☐ S Feet*
☐ SF - Surface Mount**

*Please specify required Length.

**Remote Driver.

LENS

- ☐ OP - Opal

FINISH

- ☐ WH - White
☐ BK - Black
☐ GR - Grey
☐ CF - Custom RAL#

CCT

- ☐ 30K - 3000Kelvin
☐ 35K - 3500Kelvin
☐ 40K - 4000Kelvin

*Other options are available.

OPTIONS

- ☐ No Options*
☐ 90 CRI



*Leave Empty.

LUMEN OUTPUT:



Watts	30K	35K	40K
25W	2205 lm	2250 lm	2295 lm
50W	4410 lm	4500 lm	4590 lm
75W	6610 lm	6750 lm	6890 lm

Project:

Type:

SIZE:


Diameter		
Size	Outer Lit	Inner Lit
2 Feet	27.952 Inch	25.196 Inch
3 Feet	34.250 Inch	37.795 Inch
4 Feet	46.456 Inch	44.094 Inch

RADIANCE:
OUTER LIT

INNER LIT

MOUNTING:

SUSPENDED - CEILING CANOPY

SUSPENDED - STRAIGHT WIRE*

*Remote Driver.


DROP SUSPENSION*

*Remote Driver.


SURFACE MOUNT*

*Remote Driver.