



FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency integral reflector combined with opal lens insert provide excellent lighting distribution.
- ✓ Circular internal louver is available in a wide range of finishes.
- ✓ Aluminum body of the luminaire comes with built-in-driver.
- ✓ Suitable for suspended and surface mounted installations.
- ✓ LED Spot is rated for 60,000hrs. L70 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SOURCE

- ☐ 15W LED
- ☐ 20W LED
- ☐ 25W LED

DRIVER

- ☐ ST - Standard
- ☐ DT - ELV
- ☐ DL - 0-10V Dimming (1%)
- ☐ *

* Please specify dimming method.

LOUVER

- ☐ WH - White
- ☐ BK - Black
- ☐ SL - Silver
- ☐ GL - Gold
- ☐ RG - Rose Gold

CCT

- ☐ 30K - 3000Kelvin
- ☐ 35K - 3500Kelvin
- ☐ 40K - 4000Kelvin
- ☐ DW - Dim to Warm

*Other options are available.

RADIANCE

- ☐ DD - Direct (100%Down)

*Light Distribution.

MOUNTING

- ☐ SF - Surface Mount
- ☐ S4 - Suspension 4Feet
- ☐ S6 - Suspension 6Feet
- ☐ S Feet*

* Please specify required Length.

FINISH

- ☐ WH - White
- ☐ BK - Black
- ☐ GR - Grey

OPTIONS

- ☐ No Options*
- ☐ 90 CRI

*Leave Empty.

VOLTAGE

- ☐ 120V
- ☐ 277V
- ☐ 347V*

* Not available for all configurations.

LUMEN OUTPUT:

| Watts | 30K | 35K | 40K |
|-------|---------|---------|---------|
| 15W | 1400 lm | 1430 lm | 1460 lm |
| 20W | 1910 lm | 1950 lm | 1990 lm |
| 25W | 2350 lm | 2400 lm | 2450 lm |

DIMENSIONS:

| Width | Height |
|-------|--------|
| 4.5" | 6.0" |



Project:

Type:

SPECIFICATION:

ED TUBE+

SOURCE

RADIANCE

VOLTAGE

DRIVER

MOUNTING

LOUVER

FINISH

CCT

OPTIONS

Enter the Product Code into the boxes above.