

## FEATURES:

- ✓ Architectural linear luminaire with direct or direct/indirect distribution.
- ✓ Light source: LED board (5.5"/11"/22"/24").
- ✓ Diffused illumination is provided by frosted opal lens.
- ✓ Available for row mounted installations in various lengths.
- ✓ Suitable for surface, suspended, recessed and damp area installations.
- ✓ Extruded aluminum body comes with white, black or grey finishes.
- ✓ Also available with custom color options or vinyl decals.
- ✓ LED Strips are rated for 60,000hrs. L80 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

## SIZE

\_\_\_\_\_ Feet

## SOURCE

- ☐ 5W/Ft LED  
☐ 7W/Ft LED  
☐ 10W/Ft LED\*

\* UD lighting distribution only.

## RADIANCE

- ☐ DD - Direct (100%Down)  
☐ ID - Indirect (100%Up)\*\*  
☐ UD - Uneven(70%Down/30%Up)\*\*

 \*Light Distribution.  
 \*\*Suspended Configuration only.

## VOLTAGE

- ☐ 120V  
☐ 277V  
☐ 347V\*

\*Not available for all configurations.

## DRIVER

- ☐ ST - Standard  
☐ DL - 0-10V Dimming (1%)  
☐ DA - DALI  
☐ \*  
☐ EC - Emergency Circuit  
☐ EM - Emergency\*\*

 \* Please specify dimming method (ELV).  
 \*\*Battery Pack per 4Feet section.

## LENS

- ☐ OP - Opal  
☐ PR - Prismatic  
☐ AR - Aluminum Reflector\*

\* Available for 4Feet only.

## CCT

- ☐ 30K - 3000Kelvin  
☐ 35K - 3500Kelvin  
☐ 40K - 4000Kelvin  
☐ TW - Tunable White\*\*  
 (2700K-6500K)

 \*Other options are available.  
 \*\*Available with Dali controls.

## MOUNTING

- ☐ S4-Suspension 4Feet  
☐ S6-Suspension 6Feet  
☐ S  Feet\*  
☐ WM - Wall Mount  
☐ WF - Wall Flush  
☐ SF - Surface Mount  
☐ RT - Recessed Trimless  
☐ RS - Recessed  
☐ RB - Recessed T-Bar

\*Please specify required Length.

## FINISH

- ☐ WH - White  
☐ BK - Black  
☐ GR - Grey  
☐ CF - Custom  RAL#  
☐ VD - Vinyl Decal\*

\* Please provide 600dpi Image.

## OPTIONS

- ☐ No Options\*  
☐ 90 CRI  
☐ DR - Damp Rated  
☐ DS - Daylight Sensor  
☐ DC - Dual Circuit\*\*  
☐ OS - Occupancy Sensor  
☐ DOS - Daylight & Occupancy Sensor

 \*Leave Empty.  
 \*\*Down /Up Control separately.  
 \*\*\*Combination example (90CRI/DS).

## LUMEN OUTPUT W/Ft:

Watts	30K	35K	40K
5W	515 lm	525 lm	535 lm
7W	720 lm	735 lm	750 lm
10W	1030lm	1050 lm	1080 lm

Project:

Type:

## SPECIFICATION:

ED VECTOR+

SIZE

SOURCE

RADIANCE

VOLTAGE

DRIVER

MOUNTING


LENS

FINISH

CCT

OPTIONS







Enter the Product Code into the boxes above.

**SIZE:**


Size	L (LENGTH)
1 Foot	11.75 Inch
2 Foot	24.50 Inch
3 Foot	35.50 Inch
4 Foot	48.25 Inch
5 Foot	59.25 Inch
6 Foot	72.00 Inch
7 Foot	83.00 Inch
8 Foot	95.75 Inch

**RADIANCE:**
**DIRECT DISTRIBUTION**


**UNEVEN DISTRIBUTION**

**MOUNTING:**

**SURFACE MOUNT**

**SUSPENDED**

**WALL MOUNT**

**WALL FLUSH**

**SURFACE MOUNT-90° LEFT/90° RIGHT**

**RECESSED TRIMLESS**


**SIZE:**


Size	L(CUTOUT)	L1(T-BAR)
1 Feet	11.75 Inch	11.75 Inch
2 Feet	24.50 Inch	23.75 Inch
3 Feet	35.50 Inch	35.75 Inch
4 Feet	48.25 Inch	47.75 Inch
5 Feet	59.25 Inch	59.75 Inch
6 Feet	72.00 Inch	71.75 Inch
7 Feet	83.00 Inch	83.75 Inch
8 Feet	95.75 Inch	95.75 Inch


**RADIANCE:**
**DIRECT DISTRIBUTION**

**MOUNTING:**



RECESSED



RECESSED T-BAR



90° IN (WALL TO CEILING)



RECESSED-90° LEFT/90° RIGHT