



FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: BIOS SkyBlue LED board (5.5"/11"/22").
- ✓ Circadian lighting technology with highest melanopic ratio improves daytime alertness, mood, productivity and brain function.
- ✓ Diffused illumination is provided by high efficiency opal inserted or optional low glare micropismatic lens.
- ✓ Suitable for suspended and row mounted installations.
- ✓ Fixture body with integrated driver is made from light weight steel.
- ✓ Available with matt white, black or grey finish.
- ✓ LED Strips are rated for 50,000hrs. L80 with +80 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED EDGE+ SOURCE — RADIANCE — VOLTAGE — DRIVER — MOUNTING — LENS — FINISH — CCT — OPTIONS

Enter the Product Code into the boxes above.

SOURCE

- ☐ 35W LED
- ☐ 45W LED

RADIANCE

- ☐ DD - Direct (100%Down)
- *Light Distribution.

VOLTAGE

- ☐ 120V
- ☐ 277V
- ☐ 347V*

*Not available for all configurations.
*Functionality and controls may be limited.

DRIVER

- ☐ ST - Standard
- ☐ DL - 0-10V Dimming
- ☐ DT - TRIAC
- ☐ *

* Please specify dimming method.

MOUNTING

- ☐ S4-Suspension 4Feet
- ☐ S6-Suspension 6Feet
- ☐ S Feet*
- ☐ SF - Surface Mount

*Please specify required Length.

LENS

- ☐ OP - Opal
- ☐ PR - Prismatic

FINISH

- ☐ WH - White
- ☐ BK - Black
- ☐ GR - Grey

CCT

- ☐ 30KS/BIOS - 3000K Static*
- ☐ 35KS/BIOS - 3500K Static*
- ☐ 40KS/BIOS - 4000K Static*
- ☐ 30KD/BIOS - 3000K Dynamic**
- ☐ 35KD/BIOS - 3500K Dynamic**
- ☐ 40KD/BIOS - 4000K Dynamic**

*Static-Daytime Use.
**Dynamic-Daytime/Evening Use (dims down to 2700K).

OPTIONS

- ☐ No Options*
- ☐ CB - Casambi BT
- ☐ DS - Daylight Sensor
- ☐ OS - Occupancy Sensor
- ☐ DOS - Daylight & Occupancy Sensor

*Leave Empty.
**Combination example (CB/DS).

DIMENSIONS:

Length	Width	Depth
47.25"	7.125"	2.250"

LUMEN OUTPUT:

Watts	30K	35K	40K
35W	3420lm	3500 lm	3580 lm
45W	4400 lm	4500 lm	4600 lm

